




Bearing Insert

Bearing Adapter Style - Normal Style



UK

Part No.	Dimensions (inch / mm)					Basic Load Rating lbf / N		Weight	
	d	D	B	C	h	Dynamic	Static	kg	lbs
UK 205	0.9843 25	1.8504 52	0.9055 23	0.6693 17	0.1535 3.9	2878 14000	1495 7880	0.15	0.33
UK 206	1.1811 30	2.4409 62	1.0236 26	0.7480 19	0.1969 5	4384 19500	2518 11200	0.25	0.55
UK 207	1.3780 35	2.8346 72	1.1417 29	0.7874 20	0.2244 5.7	5777 25700	3417 15200	0.37	0.81
UK 208	1.1496 40	3.1496 80	1.2205 31	0.8268 21	0.2440 6.2	6654 29600	4091 18200	0.48	1.06
UK 209	1.5748 45	3.3465 85	1.2205 31	0.8661 22	0.2520 6.4	7160 31850	4676 20800	0.53	1.17
UK 210	1.9685 50	3.5433 90	1.2598 32	0.9055 23	0.2559 6.5	7890 35100	5215 23200	0.59	1.30
UK 211	2.1654 55	3.9370 100	1.3780 35	1.0630 27	0.2756 7	9790 43550	6564 29200	0.77	1.69
UK 212	2.3622 60	4.3307 110	1.4961 38	1.0630 27	0.2992 7.6	10745 47800	7373 32800	1.03	2.26
UK 213	2.5591 65	4.7244 120	1.5748 40	1.1024 28	0.3346 8.5	12859 57200	8992 40000	1.36	2.99
UK 215	2.9528 75	5.1181 130	1.7323 44	1.1811 30	0.3622 9.2	14837 66000	11128 49500	1.67	3.67
UK 216	3.1496 80	5.5118 140	1.7717 45	1.2598 32	0.3740 9.5	16073 71500	12184 54200	1.96	4.31
UK 217	3.3465 85	5.9055 150	1.8110 46	1.3386 34	0.4016 10.2	18703 83200	14342 63800	2.42	5.32
UK 218	3.5433 90	6.2992 160	1.8504 47	1.4173 36	0.4409 11.2	21558 95900	16073 71500	3.00	6.60